

PRODUCT CHANGE NOTIFICATION

产品变更通告

July 29th, 2020 // CP-OM-D-015

Introduction:

介绍:

Yingli Green Energy Holding Company Limited, known as “YingLi Solar”, is one of the world’s leading solar module manufacturers.

Yingli will upgrade transport pallet to protect the modules.

英利绿色能源控股有限公司（以下简称“英利”）是全球领先的光伏发电产品制造商之一，现对产品变更作以下说明。

- (1) 根据 IEC61215: 2016 版新标准测试的要求，英利对其多晶系列产品的电气参数数值进行了修正。According to the new requirements of IEC61215:2016, Yingli has revised the electrical parameters of its polycrystalline products.

Module Series Affected:(涉及组件序列): YLxxxP-29b; YLxxxP-29b 1500V; YLxxxP-35b; YLxxxP-35b 1500V (xxx=Pmax)

- (2) 根据实际客户的需要，英利对于其半片系列产品的默认线长进行了约定。According to the customer requirement, Yingli upgraded the default cable length of 1/2 cell production.

注意：以上变更不涉及组件的工作性能表现。Notice: upgrade will not affect any actual performance of modules.

Descriptions:

具体变更内容:

(1) The new Voc and Isc under STC has a small increase, Max. series fuse rating was changed to 20A. Please refer to the two labels below.

(1) 新版电气参数的 STC 下开路电压和开路电流有少量提升，最大保险丝额定值变更为 20A。详见下文新旧标签图样。



Yingli Green Energy Holding Co., Ltd.

英利绿色能源控股有限公司

3399 North Chaoyang Avenue
Baoding 071051, China

中国保定国家高新区朝阳北大街 3399 号 (071051)



YINGLI ENERGY (CHINA) CO., LTD.
NO. 3399 CHAOYANG NORTH RD.
BAODING, HEBEI 071051 CHINA
TEL : +86 (312) 892 9801
FAX : +86 (312) 892 9800
yinglisolar.com

PHOTOVOLTAIC MODULE IS RATED AT AM1.5G SOLAR SPECTRUM,
1000W/m² SOLAR IRRADIANCE, AND 25°C CELL TEMPERATURE

MODULE TYPE: YL340P-35b
RATED POWER: 340.0 W(±3%) POWER SELECTION: 0/+5W
RATED VOLTAGE: 37.20 V OPEN-CIRCUIT VOLTAGE: 46.40 V (±3%)
RATED CURRENT: 9.14 A SHORT-CIRCUIT CURRENT: 9.55 A (±3%)
MAX. SERIES FUSE: 20 A MAX. SYSTEM VOLTAGE: 1000 V

PLEASE SEE THE SERIAL NUMBER ON THE FRONT SIDE OF MODULE.
FIRE RESISTANCE RATING: CLASS C



WARNING! ELECTRICAL HAZARD.
DO NOT CONNECT OR DISCONNECT UNDER LOAD.

PLEASE READ THE INSTALLATION AND USER MANUAL PRIOR TO INSTALLING,
OPERATING, OR SERVICING THIS UNIT.



MADE IN CHINA

L2004

New version 多晶 340W72 片组件 IEC 新版标签



YINGLI ENERGY (CHINA) CO., LTD.
NO. 3399 CHAOYANG NORTH RD.
BAODING, HEBEI 071051 CHINA
TEL : +86 (312) 892 9801
FAX : +86 (312) 892 9800
yinglisolar.com

PHOTOVOLTAIC MODULE IS RATED AT AM1.5G SOLAR SPECTRUM,
1000W/m² SOLAR IRRADIANCE, AND 25°C CELL TEMPERATURE

MODULE TYPE: YL340P-35b APPLICATION CLASS: A
RATED POWER: 340.0 W (0/+5W)
RATED VOLTAGE: 38.1 V OPEN-CIRCUIT VOLTAGE: 45.9 V
RATED CURRENT: 8.93 A SHORT-CIRCUIT CURRENT: 9.41 A
MAX. SERIES FUSE: 15 A MAX. SYSTEM VOLTAGE: 1000 V

PLEASE SEE THE SERIAL NUMBER ON THE FRONT SIDE OF MODULE.
FIRE RESISTANCE RATING: CLASS C



WARNING! ELECTRICAL HAZARD.
DO NOT CONNECT OR DISCONNECT UNDER LOAD.

PLEASE READ THE INSTALLATION AND USER MANUAL PRIOR TO INSTALLING,
OPERATING, OR SERVICING THIS UNIT.






MADE IN CHINA

L1901

Old version 多晶 340W72 片组件 IEC 旧版标签

(2) The default cable length is listed in the table below .but customer may get custom cable length by special noted contract.

(2) 半片组件默认（推荐）线长和安装方式如下表所示，但客户仍可根据自身需要自定义线长。

建议线长 Cable length	安装方式 Installation	涉及组件型号: Modules
1400(+)/1400(-)	横向安装 Landscape installation 	YLxxxD (36b ,40d) 1500V 1/2 LxxxCG25 (36L, 36F) -2 1/2 YLxxxC (L72, F72) 1/2 YLxxxDG25 (36L, 36F) -2 1/2 YLxxxD (L72, F72) 1/2
1200(+)/1200(-)	横向安装 Landscape installation 	YLxxxD (30b, 34d) 1500V 1/2 LxxxCG25 (30L, 30F) -2 1/2 YLxxxC (L60, F60) 1/2 YLxxxDG25 (30L, 30F) -2 1/2 YLxxxD (L60, F60) 1/2
300(+)/400(-)	纵向安装 Portrait installation 	YLxxxD (25b,30b, 36b,34d,40d) 1500V 1/2 YLxxxCG25 (30L, 30F, 36L, 36F) -2 1/2 YLxxxC (L60, F60, L72, F72) 1/2 YLxxxDG25 (30L, 30F, 36L, 36F) -2 1/2 YLxxxD (L60, F60, L72, F72) 1/2

Implementation:

具体变更时间:

Yingli Solar has scheduled to implement the aforementioned changes at the middle of August, 2020, which means customers may receive shipments of these products in end of August, 2020.

The specific transition timeline may vary among customers based on current and anticipated delivery schedules. For any technical questions, please contact: service@yingli.com. For all other inquiries, please contact your Yingli Solar sales account manager.

英利计划在 2020 年 8 月 15 日起实现上述变更,客户将在 2020 年 8 月底陆续收到带电气参数的组件产品。具体的切换时间表因不同客户当前和预期的交付时间表会有所变化,请

Yingli Green Energy Holding Co., Ltd.

英利绿色能源控股有限公司

3399 North Chaoyang Avenue

Baoding 071051, China

中国保定国家高新区朝阳北大街 3399 号 (071051)



与您的英利销售客户经理沟通。更多关于新组件产品的技术问题, 请联系: service@yingli.com。如果您有其他问题, 请联系您的英利销售客户经理。